

VILLAGE OF ELM GROVE
SEWER LATERAL DISTURBANCE & ABANDONMENT REQUIREMENTS (§232-8D)

If an existing building is razed, or remodeled in any manner resulting in the disturbance of an existing sewer lateral, there must be a complete replacement of the existing lateral with a new PVC lateral entirely at the expense of the property owner. Exceptions are allowed if all processes and procedures are complied with below.

The Director of Public Works must approve all lateral procedures and possess video documentation prior to the submission for a Demolition Permit to the Plan Commission.

Please label the video and supporting documents with:

- Owner's name
- Address
- Phone number
- Specified procedure
- Date

SUBMISSION REQUIREMENTS FOR SPECIFIED LATERAL PROCEDURES

Replacement of existing lateral with new PVC

- Submit videotape identifying the replacement with new PVC.
- Signed approval by the Department of Public Works (this sheet).

Exceptions

Exceptions may be granted by the Director of Public Works if satisfactory evidence is submitted in a timely fashion demonstrating that the existing lateral is of PVC construction **or** the existing lateral has been lined.

- Submit videotape indicating the existing lateral is entirely free from major defects.
- Signed approval by the Department of Public Works (this sheet).

Abandonment

In the event of abandonment, the lateral must be terminated at the main and permanently sealed at the main. Permanent seals and their inspections are the financial responsibility of the property owner. All sewer lateral abandonment work must be inspected and tested to the satisfaction of the Director of Public Works.

- Submit videotape identifying the permanent seal.
- Signed approval by the Department of Public Works (this sheet).

Public Way Disturbance Permit

Applicant must secure an approved Public Way Disturbance Permit from the Director of Public Works.

